

HydraX™ Fibre Optic Connectivity

Low Loss Optical adaptor



HydraX™ Fibre Optic adaptors are well suited for Telecom usage, Enterprise needs and Data Centers strict requirements.

Application

CATV

Telecommunication networks

Metro networks

Data processing networks

Premise installations

Features

Low insertion loss and back reflection loss

High precision alignment

Precision anti-rotation key and corrosion resistant body

Telcordia, ANSI, TIA/EIA, NTT and JIS compliance.

Available in SC, LC, ST, FC and MTRJ.

HydraX™ Fibre Optic Connectivity

Low Loss Optical adaptor

SPECIFICATIONS OF ADAPTOR

Temperature range	Operating	-40°C to 85°C
Insertion Loss (dB)		< 0.20 dB
Durability	1,000 matings	< 0.20 dB

Ordering Information

PRODUCT CODE	PRODUCT DESCRIPTION
AD-D100	Single mode LC/UPC duplex adaptor.
AD-D104	Multi mode OM5 LC/UPC duplex adaptor
AD-S010	Single mode SC/APC simplex adaptor
AD-D001	Multi mode SC/UPC duplex adaptor
AD-S310	Single mode FC/APC simplex adaptor
AD-S201	Multi mode ST/UPC simplex adaptor

Notes: AD-WXYZ

- 1) W = S/Simplex ; D/Duplex
- 2) X= Adapter (0/SC ; 1/LC ; 2/ST ; 3/FC ; 4/MTRJ)
- 3) Y = 0/UPC, 1/APC
- 4) Z = Type (0/singlemode, 1/multimode, 2/OM3, 3/OM4, 4/OM5)