



ChimeraX™ 1×150mm² FRT Cable

CU/XLPE/FRT/LSOH

Flame Resistant

IEC 60332-1-1

IEC 60332-1-3

IEC 60332-3-22

Design Reference

IEC60502-2:2005

Working Conditions

Storage Temperature


0°C ~ +90°C

Installation Temperature:

0°C ~ +60°C

Operation Temperature

0°C ~ +90°C



Technical data

Core No. x Cross section	1 × 150mm ² -	
Conductor Material	Class 2 circular stranding copper	
Conductor Screen	Semi-conductive compound	
Thickness of Conductor Screen (Nom.)	mm	0.7
Insulation	XLPE	
Insulation (Nom.)	mm	5.5
Insulation Scree	Semi-conductive compound	
Thickness of Insulation Scree (Nom.)	mm	0.6
Metallic Screen	Copper tape	
Thickness of Metallic Screen (Nom.)	mm	0.12
Binder	Flame retardant tape	
Thickness of Binder (Nom.)	mm	0.2
Inner Sheath	Black LSOH	
Thickness of Inner Sheath (Nom.)	mm	1.2
Armored Layer	AL tape	
No. × Thickness of Armored Layer (Nom.)	mm	2×0.5
Outer Sheath	Black LSOH with Anti-termite UV	
Thickness of Outer Sheath (Nom.)	mm	4.0
Overall Diameter (Nom.)	mm	41.2



Mechanical & Electrical Property

No.	Mechanical Specification	Unit	Designed Value
1	Rated voltage	kV	22
2	Voltage test	kV/min	The cable shall be subjected to a test voltage of 42kV , held for a period of 5 min , No breakdown shall occur
3	Partial discharge test	pC	Partial discharge magnitude shall not exceed 10 pC at 21kV
4	Max. DC resistance of conductor @20°C	Ω/km	≤0.124
5	Max. Continuous conductor temp	°C	90

Sheath Marking

The outer sheath is marked in 1meter intervals as follows

HERMESYS CHIMERAX 1×150mm² FRT CABLE WW YYYY XXXXM

Shipping Information

Packing Method

Wooden Drum with proper protection

Delivery Length
requirements

2 km per drum or according to customer

Info@hermesys.com
Phone +65 66921168
42 Emerald Hill Road, Singapore



Hermesys 2015, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Hermesys; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Hermesys. The information is believed to be correct at the time of issue. Hermesys reserves the right to amend this specification without prior notice.

www.hermesys.com