




# ChimeraX™ 144F G652D Submarine Cable

SST Unitube Triple Layers Steel Wire Armor P/N 2601DD0(82)150S2(22)



## Flame Resistant

No Request

## Design Reference

IEC 60793-1-1&2

IEC 60793-2-50

IEC 60794-1-1

IEC 60794-1-2

IEC 60794-1-21/22/23

IEC 60794-3

IEC 60794-3-30

ITU-T G.652

## Application

Under the sea or river

## Working Conditions

Storage Temperature

-30°C ~ +60°C

Installation Temperature:

-15°C ~ +45°C

Operation Temperature

-0°C ~ +30°C (In water)

-40°C ~ +70°C (In air)

## Min. Allowable Bending Radius

>1 Meter (No tensile load)

>1.2 Meter (With tensile load)

## Technical data

|                                      |                            |
|--------------------------------------|----------------------------|
| Number of Fibers                     | 144                        |
| Fiber Type                           | G652D                      |
| Fiber Tube                           | Stainless Steel Tube (SST) |
| SST OD                               | mm6.0                      |
| Inner Armor (1 <sup>st</sup> Layer)  | ϕ2.5 Galvanized Steel Wire |
| No. of Steel Wire                    | 10                         |
| Inner Sheath                         | HDPE                       |
| Middle Armor (2 <sup>nd</sup> Layer) | ϕ3.5 Galvanized Steel Wire |
| No. of Steel Wire                    | 16                         |
| Outer Armor (3 <sup>rd</sup> Layer)  | ϕ3.5 Galvanized Steel Wire |
| No. of Steel Wire                    | 22                         |
| Outer Sheath                         | PP Yarns                   |
| PP Yarns Sheath Thickness            | mm3.4                      |
| Overall Diameter (Nom.)              | mm36                       |
| Weight (In Air)                      | kg/m3.75±0.2               |
| Weight (In Seawater)                 | kg/m2.7±0.2                |

## Fiber Chromatogram

|       |      |        |        |        |       |       |                           |
|-------|------|--------|--------|--------|-------|-------|---------------------------|
| No.   | 1    | 2      | 3      | 4      | 5     | 6     | Fiber No.<br>1-12 No Ring |
| Color | Blue | Orange | Green  | Brown  | Slate | White |                           |
| No.   | 7    | 8      | 9      | 10     | 11    | 12    |                           |
| Color | Red  | Black  | Yellow | Violet | Pink  | Aqua  |                           |



|                                                                                                             |      |  |  |        |  |  |        |  |  |        |  |  |       |  |  |       |  |  |
|-------------------------------------------------------------------------------------------------------------|------|--|--|--------|--|--|--------|--|--|--------|--|--|-------|--|--|-------|--|--|
| No.                                                                                                         | 1    |  |  | 2      |  |  | 3      |  |  | 4      |  |  | 5     |  |  | 6     |  |  |
| Color                                                                                                       | Blue |  |  | Orange |  |  | Green  |  |  | Brown  |  |  | Slate |  |  | White |  |  |
| No.                                                                                                         | 7    |  |  | 8      |  |  | 9      |  |  | 10     |  |  | 11    |  |  | 12    |  |  |
| Color                                                                                                       | Red  |  |  | Black  |  |  | Yellow |  |  | Violet |  |  | Pink  |  |  | Aqua  |  |  |
| Fiber No. 13-24 1 Ring-100 , 37~48 1 Ring-60, 49~60 1 Ring-150, 73~84 1 Ring-200, 85~96 1 Ring-250          |      |  |  |        |  |  |        |  |  |        |  |  |       |  |  |       |  |  |
| No.                                                                                                         | 1    |  |  | 2      |  |  | 3      |  |  | 4      |  |  | 5     |  |  | 6     |  |  |
| Color                                                                                                       | BL   |  |  | OG     |  |  | GN     |  |  | BN     |  |  | ST    |  |  | WT    |  |  |
| No.                                                                                                         | 7    |  |  | 8      |  |  | 9      |  |  | 10     |  |  | 11    |  |  | 12    |  |  |
| Color                                                                                                       | RD   |  |  | BK     |  |  | YL     |  |  | VT     |  |  | PK    |  |  | AQ    |  |  |
| Fiber No. 25~36 2 Rings-150, 61~72 2 Rings-200, 97~108 2 Rings-60, 109~120 2 Rings-100, 121~132 2 Rings-250 |      |  |  |        |  |  |        |  |  |        |  |  |       |  |  |       |  |  |
| No.                                                                                                         | 1    |  |  | 2      |  |  | 3      |  |  | 4      |  |  | 5     |  |  | 6     |  |  |
| Color                                                                                                       | BL   |  |  | OG     |  |  | GN     |  |  | BN     |  |  | ST    |  |  | WT    |  |  |
| No.                                                                                                         | 7    |  |  | 8      |  |  | 9      |  |  | 10     |  |  | 11    |  |  | 12    |  |  |
| Color                                                                                                       | RD   |  |  | BK     |  |  | YL     |  |  | VT     |  |  | PK    |  |  | AQ    |  |  |
| Fiber No. 133~144 3 Rings-100                                                                               |      |  |  |        |  |  |        |  |  |        |  |  |       |  |  |       |  |  |

Ps: X Rings-YYY. X means the black ring quantity. YYY means the distance between the adjacent rings, unit in mm.

## Mechanical Property

| No. | Technical Parameter                        | Unit | Designed Value |
|-----|--------------------------------------------|------|----------------|
| 1   | The cable breaking load (CBL) Nom.         | kN   | 510            |
| 2   | The transient tensile strength (NTTS) Nom. | kN   | 310            |
| 3   | The operating tensile strength (NOTS) Nom. | kN   | 180            |
| 4   | Permanent Tensile Load (NPTS) Nom.         | kN   | 100            |

## Shipping Information

Packing Method

Metal Drum with both end of cable sealed with plastic cap

Delivery Length

As per customer requirement

Info@hermesys.com  
Phone +65 66921168  
42 Emerald Hill Road, Singapore



Hermesys 2015, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Hermesys; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Hermesys. The information is believed to be correct at the time of issue. Hermesys reserves the right to amend this specification without prior notice.

[www.hermesys.com](http://www.hermesys.com)