

HydraX™ Fibre Optic Closure

Dome Type Splice Closure HM-GJS-D022



HydraX™ DOME type fiber optic splice closure is also called as vertical closure, it is suitable for FTTH accessing. The input and output are on the same side. An oval hole and four round holes facilitates the operation. It is suitable for aerial, underground, conduct installation.

Features and Benefits

Heat shrinkable sealing structure.
High quality industrial plastic body material.
One oval hole and four round holes for cable entrance.
Suitable for cable diameter 5mm-38mm.
Support aerial ,underground ,pipeline , man holes , hand holes.
Protection level reaches IP68.
360 degrees access, fiber bending > 40 mm.
Maximum capacity : 144F single or 432F ribbon.
Number of trays: 6pcs * 24F.

Applications

Aerial cable installation.
Pole mounted installation.
Wall mounted installation.
Man hole and hand hole installation.
FTTH access layer.

Configuration

Material	Strengthen polymer plastic
Field Size (H*D mm)	470 * 210 mm
Max Capacity	Splice Cores : 144 cores Trays : 6 * 24F
Cable Entrance	1 * oval port ; 4 * round port
Colour	Black
Weight	2.3 kgs

Accessories

Standard	Installation bolts and nuts, Protection sleeves, Cable entry rubber, Cable tube.
Optional	Bracket for wall, pole, pressure valve... etc.