HydraX™ Surface Mount Box

6 Ports Keystone

Standard

ANSI/TIA-568.2-D

ISO/IEC 111801

RoHS Compliant | REACH Compliant

Application

Structured Cabling System

Working Condition

Storage Temperature

-10°C ~ +60°C

Installation Temperature:

0°C ~ +50°C

Operation Temperature

-10°C ~ +60°C





Technical Data

Material		ABS
Color		White
Port Count		6
Dimension (W*H*D)	mm	182.10*70.0*33.0

Ordering Information

Product Part Number	Product Description
SMB-16R1W	Hermesys HydraX™ Surface Mount Box 6 Ports Keystone

Shipping Information

Packing Method — Carton Box

Hermesys 2015, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Hermesys: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Hermesys. The information is believed to be correct at the time of issue. Hermesys reserves the right to amend this specification without prior notice.

www.hermesys.com

info@hermesys.com
Phone +65 6962 3588
27 New Industrial Rd, #06-06
Novelty Techpoint Singapore 536212

Hermesys